

DATA SHEET – 463 G

MODEL	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Merchandiser PRETZEL, rack	120V	712W	0.712 Kwh	5.93 A	50-60 Hz
Merchandiser PRETZEL SS, rack	120V	712W	0.712 Kwh	5.93 A	50-60 Hz
Merchandiser PRETZEL PT, rack	120V	712W	0.712 Kwh	5.93 A	50-60 Hz

SS = Selv-Service / PT = Pass-Thru

GENERAL FEATURES:

- > Brushed stainless steel 439, 0.5mm thick and bright stainless steel 430, 1mm thick;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray;
- > Maximum energy consumption of 0.712 Kwh;
- > 700W tubular resistance;
- > Capillary thermostat (86°F - 203°F);
- > Analog thermometer;
- > Rotary Engine 6W;
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18 AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
18" x 17.5" x 32.7"	2874.19 oz	44.1 lb	19.7" x 18.5" x 33.9"	12354.855 in ³	49 lb

