

DATA SHEET – ERATO TOWER

MODELS	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Heated Display Case AML ERATO TOWER LP	120V	707W	0.707 Kwh	5.9 A	50-60 Hz
Heated Display Case AML ERATO TOWER LC	120V	707W	0.707 Kwh	5.9 A	50-60 Hz

LC = Led with matte gray / LP = Led with bright black

GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick;
- > 4mm and 6mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.707 Kwh;
- > 700W tubular resistance;
- > Bimetal thermostat (68°F – 248°F);
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
18.5" x 17.4" x 32.3"	5173.55 oz	50.7 lb	20.3" x 20.5" x 36.3"	15106.245 in ³	58 lb

