

## DATA SHEET – 465G

| MODEL                          | TENSION | POWER RATING | CONSUMPTION | AMPERE | FREQUENCY |
|--------------------------------|---------|--------------|-------------|--------|-----------|
| Merchandiser Pizza, 3 trays    | 120V    | 713W         | 0.713 Kwh   | 5.93 A | 50-60 Hz  |
| Merchandiser Pizza SS, 3 trays | 120V    | 713W         | 0.713 Kwh   | 5.93 A | 50-60 Hz  |
| Merchandiser Pizza PT, 3 trays | 120V    | 713W         | 0.713 Kwh   | 5.93 A | 50-60 Hz  |

SS = Selv-Service / PT = Pass-Thru

### GENERAL FEATURES:

- > Brushed stainless steel 439, 0.5mm thick and bright stainless steel 430, 1mm thick;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray;
- > Maximum energy consumption of 0.713 Kwh;
- > 700W tubular resistance;
- > Capillary thermostat (86°F - 203°F);
- > Analog thermometer;
- > Rotary Engine 6W;
- > Fiberglass wire 18AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18AWG American plug NEMA 5-15P;

| SIZE                  | VOLUME (inner) | NET WEIGHT | PACKAGE               | VOLUME (outer)            | GROSS WEIGHT |
|-----------------------|----------------|------------|-----------------------|---------------------------|--------------|
| 22.5" x 20.9" x 32.3" | 4395.82 oz     | 53 lb      | 24.4" x 22.9" x 36.3" | 20282.988 in <sup>3</sup> | 62 lb        |

