

## DATA SHEET – ERATO 8BD

MODELS	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Heated Display Case AML ERATO LP 8BD, 8 trays	120V	710W	0.710 Kwh	5.91 A	50-60 Hz
Heated Display Case AML ERATO LC 8BD, 8 trays	120V	710W	0.710 Kwh	5.91 A	50-60 Hz

LC = Led with matte gray / LP = Led with bright black

### GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick;
- > Brushed stainless steel 439, 0.5mm thick trays;
- > 4mm and 6mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.710 Kwh;
- > 700W tubular resistance;
- > Bimetal thermostat (68°F – 248°F);
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
43.3" x 17.7" x 19.7"	5274.99 oz	68.4 lb	44.7" x 19.7" x 21.9"	19284.921 in <sup>3</sup>	75 lb

