

DATA SHEET – CALIOPE 8BD

| MODELS | TENSION | POWER RATING | CONSUMPTION | AMPERE | FREQUENCY |
|--|---------|--------------|-------------|--------|-----------|
| Heated Display Case AML CALIOPE LP 8BD, 8 trays | 120V | 710W | 0.710 Kwh | 5.9 A | 50-60 Hz |
| Heated Display Case AML CALIOPE LC 8BD, 8 trays | 120V | 710W | 0.0710 Kwh | 5.9 A | 50-60 Hz |

LC = Led with matte gray / LP = Led with bright black

GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick;
- > Brushed stainless steel 439, 0.5mm thick trays;
- > 4mm and 6mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.710 Kwh;
- > 700W tubular resistance;
- > Bimetal thermostat (68°F – 248°F);
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M
- > Electric cable 18AWG American plug NEMA 5-15P;

| SIZE | VOLUME (inner) | NET WEIGHT | PACKAGE | VOLUME (outer) | GROSS WEIGHT |
|-----------------------|----------------|------------|-----------------------|---------------------------|--------------|
| 43.3" x 17.7" x 19.7" | 4260.57 oz | 64 lb | 44.7" x 19.7" x 21.9" | 19284.921 in ³ | 69 lb |

